



## ZPMV2.E304660 Wiring, Printed - Component

If you notice a change to your ZPMV2 Listing Card, click [here](#) to learn more.

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

### Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

#### INFOPOWER TECHNOLOGIES LTD

E304660

SDF No F 1B, 3A & 3B, 4A & 4B

NSEZ

Gautam Budh Nagar, Noida, Uttar Pradesh 201305 INDIA

Type	Cond Width		Cond	SS/ DS/ DSO	Max Area Diam mm(in)	Max		Flame Class	Meets UL796 DSR	C T I	
	Min mm(in)	Edge mm(in)				Solder C	Oper C				
<b>Multilayer printed wiring boards.</b>											
<b>M1</b>	0.15 (0.006)	0.40 (0.016)	17.5 (0.69) Int:51	DS	50.8 (2.0)	265	10	130	V-0	All	-
<b>Single layer metal based printed wiring boards.</b>											
<b>MC</b>	0.36 (0.014)	0.50 (0.020)	35 (1.38)	SS	25.4 (1.0)	260	10	105	V-0	All	-
<b>MC2</b>	0.26 (0.010)	0.55 (0.022)	34 (1.34)	SS	50.8 (2.0)	260	20	105	V-0	All	-
<b>Single layer metal based printed wiring boards, flammability only Recognition.</b>											
<b>MC1</b>	-	-	-	SS	-	260	10	-	V-0	-	-
<b>Single layer printed wiring boards.</b>											
<b>N1</b>	0.27 (0.011)	0.77 (0.030)	33 (1.30)	SS	38.12 (1.5)	265	10	130	V-0	All	*
<b>N2</b>	0.17 (0.007)	0.53 (0.021)	17 (0.67)	DS	50.8 (2.0)	265	10	130	V-0	All	*

\* - CTI marking is optional and may be marked on the printed wiring board.



Marking: Company name or tradename "NEPL" or trademark or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2018-01-15